

1. Heater System

A: SPECIFICATIONS

Item	Specifications		Condition	
	LHD model	RHD model		
Heating capacity	4.652 kW (4,000 kcal/h, 15,872 BTU/h) or more ... When 300 m ³ (10,593 cu ft)/h		● Mode selector switch : HEAT	
			● Temp. control lever : FULL HOT	
			● Temperature difference between hot water and inlet air : 65°C (149°F)	
			● Hot water flow rate : 360 ℓ (95.1 US gal, 79.2 Imp gal)/h	
Air flow rate	300 m ³ (10,593 cu ft)/h	280 m ³ (9,887 cu ft)/h	Heat mode (FRESH), FULL HOT at 12.5 V	
Max air flow rate	510 m ³ (18,008 cu ft)/h	480 m ³ (16,949 cu ft)/h	● Temperature control lever : FULL COLD	
			● Blower fan speed : 4th position	
			● RECIRC switch position : RECIRC	
Heater core size (height x length x width x thickness)	193.5 x 152.0 x 25.0 x 0.9 mm (7.62 x 5.98 x 0.984 x 0.035 in)	159.5 x 180 x 32.0 x 1.0 mm (6.28 x 7.09 x 1.26 x 0.039 in)	—	
Blower motor	Type	Magnet motor 230 W or less	Magnet motor 220 W or less	at 12 V
	Fan type and size (diameter x width)	Sirocco fan type 150 x 75 mm (5.91 x 2.95 in)	Sirocco fan type 140 x 65 mm (5.51 x 2.56 in)	—