

1. Heater System

A: SPECIFICATIONS

Item	Specifications		Condition
	LHD model	RHD model	
Heating capacity	4.652 kW (4,000 kcal/h, 15,872 BTU/h) or more ... When 300 m ³ (10,593 cu ft)/h		<ul style="list-style-type: none"> ● Mode selector switch : HEAT ● Temp. control lever : FULL HOT ● Temperature difference between hot water and inlet air : 65°C (149°F) ● Hot water flow rate : 360 ℥ (95.1 US gal, 79.2 Imp gal)/h
Air flow rate	300 m ³ (10,593 cu ft)/h	280 m ³ (9,887 cu ft)/h	Heat mode (FRESH), FULL HOT at 12.5 V
Max air flow rate	510 m ³ (18,008 cu ft)/h	480 m ³ (16,949 cu ft)/h	<ul style="list-style-type: none"> ● Temperature control lever : FULL COLD ● Blower fan speed : 4th position ● RECIRC switch : RECIRC position
Heater core size (height x length x width x thickness)	193.5 x 152.0 x 25.0 x 0.9 mm (7.62 x 5.98 x 0.984 x 0.035 in)	159.5 x 180 x 32.0 x 1.0 mm (6.28 x 7.09 x 1.26 x 0.039 in)	—
Blower motor	Type	Magnet motor 230 W or less	Magnet motor 220 W or less at 12 V
	Fan type and size (diameter x width)	Sirocco fan type 150 x 75 mm (5.91 x 2.95 in)	Sirocco fan type 140 x 65 mm (5.51 x 2.56 in) —