7. Customizing Function

A: GENERAL

• The following system can be customized by using a SUBARU select monitor.

System name			Initial setting	Customized settings
Room light (delayed extinguish- ment)	Illuminating time after door closed		5 seconds	0 seconds (OFF)
				3 seconds (short)
				8 seconds (long)
	Illuminating time after keyless unlock operation		20 seconds	0 seconds (OFF)
				10 seconds (short)
				30 seconds (long)
Keyless entry system	Answer back buzzer	Existence set- ting	Yes	No
		ON/OFF	ON	OFF
	Hazard answer back		ON	OFF
Alarm system	Warning	ON/OFF	ON	OFF
		Monitoring de- lay setting	30 seconds	0 seconds
	Impact sensor	Existence set- ting	No	Yes
		ON/OFF	OFF	ON
	Passive arming switching		OFF	ON
Rear defogger timer			OFF after 15 minutes	Operates for 15 minutes or continuously
Wiper deicer			OFF after 15 minutes	Operates for 15 minutes or continuously
Lockout prevention			ON	OFF
Battery drain prevention			ON	OFF

^{*:}Setting is possible only with SUBARU select monitor.

NOTE:

Items above must be set to coincide with the vehicle's equipment and specifications for normal operation and diagnosis.